

# STORAGE SHELVES MESH WELDING LINE

GWC1200ZG-02




Jiaoyang Welding Industries Hebei Co., Ltd.

ADD: No. 28, Wei'Er Road, Eastern Industrial Zone, Anping County, Hebei Province, China ,053600 TEL: +86-318-7063110 FAX:+86-318-7800251 web:www.jiaoyangen.net



#### Layout



1 Line wire payoff

- ②Line wire detection
- 3 Line wire straightening
- **4** Line wire storage loop
- **5** Main welding machine
- 6 Double-layer cross wire pre-loading hopper
- Servo motor pull mesh
- 8 Auto.mesh cutting
- **⑨Auto.mesh falling device**




# BASIC TECHNICAL PARAMETERS

MODEL NO.	GWC1200ZG-02
Mesh width	1200mm
Wire diameter	Line wire 4-6mm Cross wire 2-4mm
Mesh length	≤2000mm
No. of electrodes	8pcs
Cross wire space	15-200mm
Transformer	IF 180KVAx2sets
Line wire space	50-300mm
Tolerance of diagonal line	±1mm
Welding speed	80times/min
Welding material	Low carbon steel wire




# Line wire feeding



>The wire payoff adopt double layer which loading capacity is 500kg, save covering space.



#### Line wire detection




>It will automatically alarm and stop running when lacking of material, so avoid to waste material.

TEL: +86-318-7063110 FAX:+86-318-7800251 web:www.jiaoyangen.net



# Line wire straightening



>It adopt two directions of 45° straightening, which will reduce the material prestress and the flatness of mesh will be ensured.

TEL: +86-318-7063110 FAX:+86-318-7800251 web:www.jiaoyangen.net




## Line wire storage loop



>The storage loop can reduce the resistance of pulling mesh, which can make the mesh size accurate and pulling mesh speed.






- >IF welding, no burnt and mesh flatness.
- >Can realize the side wire welding from the opposite direction.
- >Pneumatic pressure, which can ensure the welding pressure even and stable.
- >It adopt cycled water cooling to prolong the electrodes working life.



#### Double layer cross wire hopper



>The upper and lower hoppers adopt chain drive for feeding, and the storage capacity is 300kg.

>Two different sizes of wire diameter can be produced on one piece of mesh.



#### Servo motor pull mesh



>The distance of servo motor pull mesh is 2.1m, with high accuracy and fast speed, it can pull out 4pcs of mesh at the same time to space saving.

>The servo motor pull mesh unit and the main welding machine can be separated, which is convenient for personnel to adjust and maintain.

>It can automatically cut the cross wire edges and no need to process manually anymore.



## Auto.mesh cutting without edges



>The mesh cutting speed is 80 times /min and can realize the finished mesh without edges after cutting as requirements,no need to process manually anymore.



Auto.mesh falling device



>It adopt side mesh output structure after falling, and equipped with 2pcs mesh falling trolleys to be used alternately, and the stacking height is 800mm.



Jiaoyang Welding Industries Hebei Co., Ltd.

TEL: +86-318-7063110 E-mail:joy@jiaoyangen.net

ADD: No. 28, Wei'Er Road, Eastern Industrial Zone, Anping County, Hebei Province,

China ,053600 FAX:+86-318-7800251 web:www.jiaoyangen.net