

REINFORCEMENT MESH WELDING PRODUCTION LINE

GWC500CJ×2-02




Jiaoyang Welding Industries Hebei Co., Ltd.

ADD: No. 28, Wei'Er Road, Eastern Industrial Zone, Anping County, Hebei Province , China ,053600TEL: +86-318-7063110FAX:+86-318-7800251web:www.jiaoyangen.net



Layout



1.line wire tranferring and laying device 2.wire straightening and cutting machine

- 3.line wire feeding device
 - aaa wira baanar
- 4.welding machine

- 5. cross wire hopper
- 7.fast second pulling device
- 9.mesh fallen device

- 0
- 6. pulling device
- 8. wire payoff



Technical Parameters

MODEL NO.	GWC500CJ×2-02
Width 500mm	×2
Cross wire spacing	≥50mm
Number of welding electrodes	8+8
Cross wire feeding	Pre cut /coil
Transformer	125KVA×4
Diagonal tolerance	±2mm(2m mesh length)
Wire diameter	4-8mm
Wire material	Low carbon steel wire
Welding speed	8-10panels/min(2m mesh length)
Mesh form	Mesh length ≤6m
Line wire feeding	coil
Line wire spacing	50mm



Detailed Introduction Line wire laying device


>This device will lay the pre cut line wire according the line wire spacing.

>And do the arrangement for the next feeding process.



Detailed Introduction

Line wire straightening machine



>Line wire straightening and cutting machine is integrated with welding

machine. Equip 2 sets , 1 set on left side , the other set on right side.

>Pre cut line wire will be transferred to next step.


Jiaoyang Welding Industries Hebei Co., Ltd.

ADD: No. 28, Wei'Er Road, Eastern Industrial Zone, Anping County, Hebei Province , China ,053600TEL: +86-318-7063110FAX:+86-318-7800251web:www.jiaoyangen.net



Detailed Introduction

Line wire feeding device




>With automatic robotic pneumnatic grippers for picking up line wires from the

wire delivery table and feeding the wires to the welding machine

>With picking detection device, picking fails and it will pick again automaticly.

Then feeding wires to welding machine automaticly.





>Welding system adopst modular unit , and it will be more simple to adjust line


wire spacing.

>Welind electrodes is CrZrCu with the best Hardness and conductivity .

Transformer with power 125KVA is with water cooling system, which makes

use life longer.





>Load about 150kgs wire

>Wire drops driven by step motor .

>It is installed on the pulling device, which can away from the welding machine.

It will more convenient to do repairing and adjustment.



Detailed Introduction


Mesh pulling device



>After mesh welded, it will be pulled .

>out ,driven by servo motor with precise size.





>Max mesh panel length is at 6m

>It is composed of dustpan type supporting plates both sides and C-type frame

>Receiving structure can be feeely adjusted according the mesh width.



Jiaoyang Welding Industries Hebei Co., Ltd. TEL: +86-318-7063110 E-mail:joy@jiaoyangen.net ADD: No. 28, Wei'Er Road, Eastern Industrial Zone, Anping County, Hebei Province , China ,053600 FAX:+86-318-7800251 web:www.jiaoyangen.net