

WIRE STRAIGHTENING AND CUTTING MACHING



Parameters	GTQ3-6	GTQ4-8	GTQ5-12	GTQ8-14	GTQ10-16
Wire diameter	3-6mm	4-8mm	5-12mm	8-14mm	10-16mm
Working speed	110m/min	110m/min	130m/min	130m/min	130m/min
Wire straightness	≤2mm/m	≤2mm/m	≤2mm/m	≤2mm/m	≤2mm/m
Wire type	coil	coil	coil	coil	coil
Cutting length	0.5-6m	0.5-6m	0.8-12m	0.8-12m	0.8-12m
Cutting method	Servo cutting	Servo cutting	Servo cutting	Servo cutting	Servo cutting
Wire material	Low carbon steel wire galvanized wire	Cold rolling ribbed wire		Cold rolling smooth wire	
Wire pressure	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Cutting tolerance	±0.5mm/m	±1mm/m	±1mm/m	±1mm/m	±1mm/m
Total power capacity	10.5KW	25KW	37.5KW	44.5KW	52.5KW
Power supply	3phase380V50HZ	3phase380V50HZ	3phase380V50HZ	3phase380V50HZ	3phase380V50HZ

A/B

C/D

ZB

ZY

CH/BH

ZW

GTQ

Other